

Analysis of Metals in Soils from Small Arms Ranges Using Incremental Sampling

Presenter

Thomas Georgian, Ph.D.

Chemist, Environmental and Munitions
Center of Expertise

US Army Engineering and Support
Center, Huntsville

EMDQ Workshop

28 March – 1 April 2011




US Army Corps of Engineers
BUILDING STRONG®



Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 MAR 2011		2. REPORT TYPE		3. DATES COVERED 00-00-2011 to 00-00-2011	
4. TITLE AND SUBTITLE Analysis of Metals in Soils from Small Arms Ranges Using Incremental Sampling				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Engineering and Support Center,Environmental and Munitions Center of Expertise,PO Box 1600,Huntsville,AL,35807				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES Presented at the 2011 DoD Environmental Monitoring & Data Quality Workshop (EMDQ 2011), 28 Mar ? 1 Apr, Arlington, VA.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 17	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Feedback for 2010 EDQM Workshop



- More focus on case studies... Less theory...
- There seemed to be a lot more...statistics...Too much theory...
- Similar comments for 2009 Workshop

... Thomas Georgian - great presenter! ALMOST made me want to be a statistician, then I regained my senses.



Warning !



The following presentation contains information of a factual nature and mature technical content that may not be suitable for all audiences. If you are easily disturbed by use of strong scientific language, excessive mathematics, or graphic uncensored data of an explicitly statistical nature, viewer discretion is strongly advised.




Probabilistic evaluations and
Gy's sampling theory used
extensively.



Case Study Site Investigation (SI) of “Site X”

- 20,000-acre site with multiple skeet & small arms ranges.
- Stratified into ¼-acre Sampling Units (SUs) with highest suspected levels of contamination.
- 2-kg incremental samples (IS) of 100 increments from surface soils (0 – 2 inches) tested for metals (e.g., Cu, Pb, Zn & Sb) by Method 6010B, as well as PAHs by 8270C-SIM and explosives by 8330B.
- Splits of unground & ground lab sub-samples (steel puck mill in Method 8330B) analyzed.





Replicate IS Samples (Unground) from SU with Small Arms Berm

Metal	IS Field Replicates (mg/kg) <i>n</i> = 7 (MRS05, SU#5)							Mean (mg/kg)	%RSD
Pb	170	200	660	240	160	130	380	277	68%
Cu	40	50	51	72	31	34	53	47	29%

Pb Screening Limit (SL) = 400 mg/kg.

Pb Concentrations (*x*) \approx 100 – 700 mg/kg.

%RSD > 30% → Distribution not normal (but lognormal)

**Are data usable to determine if site is “clean”
or “dirty”?**



Evaluating RSDs > 30%

- Work Plan:

Provided...the calculated RSD is lower than the stated RSD [< 20 for lab triplicates, < 30 for field replicates]... the samples...can be reasonably assumed to be representative of the site conditions...

- Post-sampling: %RSD = 100% - 200% for replicates.

Excerpt from contractor's tech memo: Whether [large %RSDs are] ...appropriate...depends on...how close to a decision limit a concentration result might be. **It does not mean...data should be automatically rejected if the %RSD is greater [than 30%].**

**I'm OK; you're OK,
even though your %RSDs are not OK.**



Technical Project Planning (TPP)




- 7-Step DQO Process implemented.

► $H_0: \mu \geq \text{Screening Level (SL)}$

Reject H_0 (i.e., conclude SU “clean”) if 95% UCL < SL.

Large variability (e.g., %RSD) increases UCL; RI needed if $\bar{x} < \text{SL} < \text{UCL}$ to determine if the site is “dirty.”

Example: Pb for MRS05, SU5 - Is site “dirty” or “clean”?



Laboratory IS Sub-samples

Metal	IS Field Replicates (mg/kg) <i>n</i> = 7 (MRS05, SU#5)							Mean (mg/kg)	%RSD
Pb	170	200	660	240	160	130	380	277	68%
Cu	40	50	51	72	31	34	53	47	29%

**Sample used to
prepare lab triplicates**



Sub-sampling (within-sample) Variability

Metal	Laboratory Triplicate Sub-samples			Mean	%RSD
	1 st Field Replicate (mg/kg)			(mg/kg)	
Pb	170	1,900	570	880	103
Cu	40	46	59	48	12


**Results not quantitatively reliable;
Pb varies by order of magnitude within single sample !**

$\sigma_{\text{Total}} \approx 190$ ppm (Total variability, $n = 7$)
 $< \sigma_{\text{Lab}} \approx 940$ ppm (Lab sub-sampling variability, $n = 3$) !


- σ_{Total} biased low; $n = 7$ unground field replicates too small to reliably estimate σ_{Total} and do statistical evaluations.




Ground vs. Unground Pb (Same IS)



Method Blanks (Ground Glass)




Ground vs. Unground IS Field Replicates for Pb




Boxplot of Pb, Skeet Range at Fort Eustis ("DU 4")

n = 5 2.5-g Ground & Unground Laboratory Sub-samples from IS (100 increments).



Boxplot of Pb, Skeet Range at Fort Eustis ("DU 4")



Conclusions

- %RSD measures variability **not usability**.
 - ▶ Do not set arbitrary goals for %RSD. Use %RSD to qualitatively assess precision only.
 - ▶ Use 7-Step DQO Process to develop sampling design and evaluate usability.
- Large number of increments of limited value if lab sub-sampling variability is large (because soils with metal particles are not ground).
- Even IS approach with grinding may not be adequate if n is small.



Questions?

